



Proof, Photo & Production media PRODUCT DATASHEET



EFI Photo Paper 1260 Semimatt

Universal heavy weight semimatt photo paper, PE microporous coating, with a very low content of optical brighteners, especially suitable for professional photo prints and contract proofing applications. This paper is almost without optical brighteners and very suitable for offset applications. The 1260 is FOGRA Cert. according to ISO 12647-7 (semi matte) and delivered with the EFI-FOGRA backside print.



Description:

Heavy weight semimatt photo paper
High resolution
Photorealistic prints
Suitable for cold and hot lamination
Almost no optical brighteners
FOGRA-certificated (ISO 12647-2 PT1 and PT2)

Application:

Photo
Proofing

Technical data:

Weight	250	g / m ²
Thickness	270	μ
Opacity	96	%
Gloss [Tappi 75°]	47	%
L*a*b* Paper white	94,78 / -0,23 / -3,87	
Storage	15 -30	°C (40 - 60% RH)

Size

Sheet	Roll	Core
DIN A4 (210 x 297 mm)	25,4 cm x 25 m (10")	3" *) 61,0 cm x 25 m (24") 3" *)
SUPER A4 (241 x 340 mm)	32,9 cm x 10 m (13")	2" 91,4 cm x 25 m (36") 3" *)
DIN A3 (297 x 420 mm)	32,9 cm x 25 m (13")	3" *) 106,7 cm x 25 m (42") 3" *)
DIN A3+ (330 x 483 mm)	36,0 cm x 25 m (14,17")	3" *) 111,8 cm x 25 m (44") 3" *)
DIN A2 (420 x 594 mm)	43,2 cm x 25 m (17")	3" *) 127,0 cm x 25 m (50") 2"
DIN A1 (594 x 841 mm)	50,8 cm x 25 m (20")	3" *) *) supplied with each two adapters 3" to 2" core



Important: Before using our print media, please verify that it is suitable for use with your printer. We shall not assume liability for non-performance of the print media resulting from changes beyond our control in printing inks or printers. Specifications are subject to change without notice. This product data sheet is intended to be used as a guideline only. Storing conditions: Please keep product in the supplied boxes for best possible protection. Product must be stored in a cool and dry environment, exposure to sun light is to be avoided.